

ENVIRONMENTAL PRODUCT DECLARATION

as per /ISO 14025/ and /EN 15804/

Owner of the Declaration	Cementa AB, HeidelbergCement Group
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-HCG-20190142-CAA1-EN
Issue date	21/11/2019
Valid to	20/11/2024

Portland Fly Ash Cement CEM II/A-V 52.5 N
(Bascement)
Cementa AB, HeidelbergCement Group

www.ibu-epd.com / <https://epd-online.com>



General Information

<p>Cementa AB, HeidelbergCement Group</p> <hr/> <p>Programme holder IBU - Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany</p> <hr/> <p>Declaration number EPD-HCG-20190142-CAA1-EN</p> <hr/> <p>This declaration is based on the product category rules: Cement, 07.2014 (PCR checked and approved by the SVR)</p> <hr/> <p>Issue date 21/11/2019</p> <hr/> <p>Valid to 20/11/2024</p> <hr/> <div style="text-align: center;">  </div> <hr/> <p>Dipl. Ing. Hans Peters (President of Institut Bauen und Umwelt e.V.)</p> <hr/> <div style="text-align: center;">  </div> <hr/> <p>Dr. Alexander Röder (Managing Director IBU)</p>	<p>CEM II/A-V 52.5 N</p> <hr/> <p>Owner of the declaration Cementa AB Marieviksgatan 25, Box 47210 SE-100 74 Stockholm</p> <hr/> <p>Declared product / declared unit 1 metric t of CEM II/A-V 52.5 N</p> <hr/> <p>Scope: This Environmental Product Declaration (EPD) covers the product life cycle stages A1-A3. It is valid for CEM II/A-V 52.5 N bulk Portland cement, manufactured by Cementa AB in the plant Slite, Sweden, in 2018. This analysis relies on transparent, plausible and documented basis data. All the model assumptions, which influence the results, are declared. The life cycle assessment is representative of the products introduced in the declaration for the given system boundaries.</p> <p>The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.</p> <hr/> <p>Verification</p> <table border="1"> <tr> <td colspan="2">The standard /EN 15804/ serves as the core PCR</td> </tr> <tr> <td colspan="2">Independent verification of the declaration and data according to /ISO 14025:2010/</td> </tr> <tr> <td><input type="checkbox"/> internally</td> <td><input checked="" type="checkbox"/> externally</td> </tr> </table> <hr/> <div style="text-align: center;">  </div> <hr/> <p>Dr. Eva Schmincke (Independent verifier appointed by SVR)</p>	The standard /EN 15804/ serves as the core PCR		Independent verification of the declaration and data according to /ISO 14025:2010/		<input type="checkbox"/> internally	<input checked="" type="checkbox"/> externally
The standard /EN 15804/ serves as the core PCR							
Independent verification of the declaration and data according to /ISO 14025:2010/							
<input type="checkbox"/> internally	<input checked="" type="checkbox"/> externally						

Product

Product description / Product definition

Cement is a hydraulic binder. It consists of finely ground, non-metallic inorganic compounds. Cement is produced by grinding cement clinker and other main or minor constituents. When water is added to cement, a cement paste is formed, which sets and hardens by means of hydration reactions. After hardening, it retains its strength and stability even under water. The declared product is a cement conforming with the composition of Portland fly ash cement CEM II/A-V 52.5 N manufactured by Cementa in the plant Slite in 2018. The calculation is based on plant-specific data. The considered cement belongs to the main cement type CEM II in accordance with /EN 197-1/.

For the placing on the market of the product in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Regulation /EU) No. 305/2011 Construction Product Regulation (CPR)/ applies. The product needs a Declaration of Performance taking into consideration /EN 197-1/ and the CE-marking. For the application and use the respective national provisions apply.

Application

The application of cement has a large variety. It is mainly used as a binder for concrete and mortar. The application in concrete is regulated in /EN 206/. According to this standard, general suitability is established for cement conforming to /EN 197-1/.

Technical Data

The declared cement corresponds to the 52.5 standard compressive strength class with ordinary early strength development (N) in accordance with /EN 197-1/.

Constructional data

Name	Value	Unit
Strength class acc. to /EN 197-1/	52.5	N/mm ²

Performance data of the product in accordance with the Declaration of Performance with respect to its Essential Characteristics according to /EN 197-1/.

Base materials / Ancillary materials

Clinker: 80 - 94 %
Cement clinker is made of a raw material mixture that is added to the cement kiln and sintered at a temperature of 1400 °C. The basic materials for the production of cement clinker consist of calcium oxide (CaO), silicon dioxide (SiO₂), small amounts of aluminium oxide (Al₂O₃) and iron oxide (Fe₂O₃). Raw materials that provide these constituents are limestone, chalk and clay or limestone marl as its natural occurring mixture.

Fly ash: 6 - 20 % Fly ash is a by-product of coal-fired power generation. It is obtained by electrostatic or mechanical precipitation of dust-like particles from the flue gases. Fly ash V is siliceous in nature having pozzolanic properties. It mainly consists of reactive silicon dioxide (SiO₂ ≥ 25 % by mass) and aluminium oxide (Al₂O₃). Minor constituents are iron oxide

(Fe₂O₃), calcium oxide (CaO) and other compounds. The CaO content is restricted according to /EN 197-1/.

Gypsum/Anhydrite/Residual gypsum: 0 - 5 %
Gypsum and anhydrite are added as setting regulators to cement. Many cement plants use residual gypsum from flue gas desulfurization as well.

This product contains substances listed in the candidate list (date: 21.11.2019) exceeding 0.1 percentage by mass: no

Reference service life

This study covers the production stage information (from A1 to A3) of the product. As no use stage is declared, the reference service life for cement is irrelevant.

LCA: Calculation rules

Declared Unit

The declared unit is 1 metric t of CEM II/A-V 52.5 N.

Declared unit

Name	Value	Unit
Declared unit	1	t
Conversion factor to 1 kg	0.001	-

with the official regulations, regular data collections are established at HeidelbergCement group. The emission data of the clinker burning process are included in this LCA study. Preferably directly measured kiln emission values in the specific plant are considered. Noise, landscape impact, vibration etc. are not within the scope of this study. In case that specific kiln emission data are not available, default values are automatically used by the /GCCA/ tool.

System boundary

Type of EPD: cradle to gate

For the modelling of cement both specific production data from HeidelbergCement and background data (especially for upstream processes) have been used. For life cycle modelling of the considered product, the verified Global Cement and Concrete Association /GCCA/ online tool for EPDs of concrete and cement is used. The tool was developed by Quantis and is owned by the Global Cement and Concrete Association. The life cycle assessment in the tool has been implemented in compliance with /EN 15804/, the General Programme Instructions (GPI 2.5) for the International EPD® System, the product category rules /UN CPC 375 Concrete/ and /UN CPC 3744 Cement/. For the present study, version 1.5 of the CSI tool was used, largely being based on the database /ecoinvent v3.3/.

The selected system boundaries comprise the production of cement including raw material extraction up to the finished product at the factory gate.

The product stage contains:
Module A1: Extraction and processing of raw materials.
Module A2: Transport of raw materials to the factory gate and internal transport.
Module A3: Cement production.
The construction stage, the use stage and the disposal stage are not included in the life cycle assessment of cement.

A significant factor regarding primary data collection is the emission measurement directly at the plant. In line

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

The development of scenarios shall be made on the finished product (e.g. concrete) and not on the upstream product cement.

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MNR	MNR	MNR	MND	MND	MND	MND	MND	MND	MND

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 metrich t CEM I 52.5 R

Parameter	Unit	A1-A3
Global warming potential	[kg CO ₂ -Eq.]	6.99E+2
Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	9.62E-6
Acidification potential of land and water	[kg SO ₂ -Eq.]	6.51E-1
Eutrophication potential	[kg (PO ₄) ³ -Eq.]	2.71E-1
Formation potential of tropospheric ozone photochemical oxidants	[kg ethene-Eq.]	8.24E-2
Abiotic depletion potential for non-fossil resources	[kg Sb-Eq.]	1.65E-4
Abiotic depletion potential for fossil resources	[MJ]	1.37E+3

RESULTS OF THE LCA - RESOURCE USE: 1 metrich t CEM I 52.5 R

Parameter	Unit	A1-A3
Renewable primary energy as energy carrier	[MJ]	4.11E+2
Renewable primary energy resources as material utilization	[MJ]	0.00E+0
Total use of renewable primary energy resources	[MJ]	4.11E+2
Non-renewable primary energy as energy carrier	[MJ]	2.06E+3
Non-renewable primary energy as material utilization	[MJ]	0.00E+0
Total use of non-renewable primary energy resources	[MJ]	2.06E+3
Use of secondary material	[kg]	1.24E+2
Use of renewable secondary fuels	[MJ]	8.85E+2
Use of non-renewable secondary fuels	[MJ]	1.07E+3
Use of net fresh water	[m ³]	5.21E+0

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

1 metrich t CEM I 52.5 R

Parameter	Unit	A1-A3
Hazardous waste disposed	[kg]	0.00E+0
Non-hazardous waste disposed	[kg]	4.34E+2
Radioactive waste disposed	[kg]	0.00E+0
Components for re-use	[kg]	0.00E+0
Materials for recycling	[kg]	2.75E-1
Materials for energy recovery	[kg]	0.00E+0
Exported electrical energy	[MJ]	0.00E+0
Exported thermal energy	[MJ]	0.00E+0

Remark to Global warming potential:

This includes 82.1 kg CO₂-eq. from the incineration of wastes in clinker production. According to the "polluter-pays-principle" /EN 15804/ that would be assigned to the production system, which has caused the waste. In this EPD the CO₂ contribution is not subtracted. This is to ensure comparability across countries of calculated global warming potentials for cements even if the used secondary fuels in other countries do not have waste status.

Remark to Waste categories:

The waste indicators account for wastes from clinker and cement manufacturing only.

References

/IBU 2016/

IBU (2016): General Programme Instructions for the Preparation of EPDs at the Institut Bauen und Umwelt e.V., Version 1.1 Institut Bauen und Umwelt e.V., Berlin.
www.ibu-epd.de

/ISO 14025/

DIN EN /ISO 14025:2011-10/, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

/EN 15804/

/EN 15804:2012-04+A1 2013/, Sustainability of construction works — Environmental Product

Declarations — Core rules for the product category of construction products

/Candidate List of Substances of Very High Concern for Authorisation/

European Chemical Agency, 2019

www.echa.europa.eu/web/guest/candidate-list-table

/ecoinvent v3.3/

ecoinvent database, version 3.3, 2016

<https://www.ecoinvent.org/>

/EN 197-1/

/EN 197-1:2011/, Cement - part 1: Composition specification and conformity criteria for common cements

/EN 206/

/EN 206:2013/, Concrete: Specification, performance, production and conformity

/(EU) No. 305/2011 (CPR)/

Regulation (EU) No 305/2011 of the European Parliament and of the council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

/General principles/

for the EPD range of Institut Bauen und Umwelt e.V. (IBU), 2013-04

www.ibu-epd.com

/GCCA/

Global Cement and Concrete Association

<https://gccassociation.org/>

/PCR 2012:01/

Product Category Rules according to ISO 14025: Construction products and construction services, version 2.01, 2012:01

<http://environdec.com/en/PCR/Detail/?Pcr=8098>

/UN CPC 3744 Cement/

Product Category Rules for Cement, 2010,

<http://environdec.com/en/PCR/Detail/pcr2010-09>

/UN CPC 375 Concrete/

Product Category Rules for Unreinforced Concrete, WBCSD Cement Sustainability Initiative, 2013

<http://environdec.com/en/PCR/Detail/pcr2013-02>

**Publisher**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 - 3087748 - 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

HEIDELBERGCEMENT**Author of the Life Cycle
Assessment**

HeidelbergCement AG
Oberklamweg 6
69181 Leimen
Germany

Tel +49 6221 481 13719
Fax +49 6221 481 13757
Mail martina.dietermann@heidelbergcement.com
Web www.heidelbergcement.com

CEMENTA
HEIDELBERGCEMENT Group**Owner of the Declaration**

Cementa AB, HeidelbergCement
Group
Marieviksgatan 25
11743 Stockholm
Sweden

Tel +46 8 625 68 00
Fax +46 8 753 36 20
Mail bodil.wilhelmsson@cementa.se
e
Web www.cementa.se